

Package ‘orloca’

May 16, 2023

Type Package

Depends methods, png, ucminf

Imports grDevices, graphics, knitr, rmarkdown, stats

Suggests orloca.es, testthat (>= 3.0.0)

ByteCompile true

VignetteBuilder knitr

Title Operations Research LOCational Analysis Models

Version 5.3

Date 2023-05-16

Encoding UTF-8

Author Manuel Munoz-Marquez <manuel.munoz@uca.es>

Maintainer Manuel Munoz-Marquez <manuel.munoz@uca.es>

Description Objects and methods to handle and solve the min-sum location problem, also known as Fermat-Weber problem. The min-sum location problem search for a point such that the weighted sum of the distances to the demand points are minimized. See “The Fermat-Weber location problem revisited” by Brimberg, *Mathematical Programming*, 1, pg. 71-76, 1995. <[DOI:10.1007/BF01592245](https://doi.org/10.1007/BF01592245)>. General global optimization algorithms are used to solve the problem, along with the ad-hoc Weiszfeld method, see “Sur le point pour lequel la Somme des distances de n points donnees est minimum”, by Weiszfeld, *Tohoku Mathematical Journal, First Series*, 43, pg. 355-386, 1937 or “On the point for which the sum of the distances to n given points is minimum”, by E. Weiszfeld and F. Plastria, *Annals of Operations Research*, 167, pg. 7-41, 2009. <[DOI:10.1007/s10479-008-0352-z](https://doi.org/10.1007/s10479-008-0352-z)>.

Language en, es

License GPL (>= 3)

URL <http://knuth.uca.es/orloca/>

RoxygenNote 7.2.3

Repository CRAN

Repository/R-Forge/Project orloca

Repository/R-Forge/Revision 61

Repository/R-Forge/DateTimeStamp 2023-05-16 09:46:31

Date/Publication 2023-05-16 11:10:02 UTC

NeedsCompilation no

R topics documented:

orloca-package	2
andalusia	4
as-methods	5
as.data.frame.loca.p	6
as.loca.p	7
as.loca.p.data.frame	8
as.loca.p.matrix	9
as.matrix.loca.p	10
contour.loca.p	11
distsum	12
distsumgra	13
distsummin	14
loca.p	16
persp.loca.p	17
plot	18
rloca.p	19
zsum	21
zsumgra	21
zsummin	22
Index	23

orloca-package

Operations Research LOCational Analysis Models

Description

Objects and methods to handle and solve the min-sum location problem, also known as Fermat-Weber problem.

Details

The min-sum location problem search for a point such that the weighted sum of the distances to the demand points are minimized. See "The Fermat-Weber location problem revisited" by Brimberg, *Mathematical Programming*, 1, pg. 71-76, 1995, [doi:10.1007/BF01592245](https://doi.org/10.1007/BF01592245).

General global optimization algorithms are used to solve the problem, along with the adhoc Weiszfeld method, see "Sur le point pour lequel la Somme des distances de n points donnees est minimum", by E. Weiszfeld, *Tohoku Mathematical Journal, First Series*, 43, pg. 355-386, 1937 or "On the point for which the sum of the distances to n given points is minimum", by E. Weiszfeld and F. Plastria, *Annals of Operations Research*, 167, pg. 7-41, 2009, [doi:10.1007/s104790080352z](https://doi.org/10.1007/s104790080352z).

Package: orloca
Type: Package
Version: 5.3
Date: 2023-05-16
License: GPL (>= 3)

The package provides a class (`loca.p`) that represents a location problem with a finite set of demand points over the plane. Also, it is possible to plot the points and the objective function. Such objective function is the total weighted distances travelled by all the customers to the service.

Non-planar location problems could be handle in future versions of the package.

For a demo, load the package with `library(orloca)`, and use `demo(orloca)`.

The package is ready for internationalization. The author ask for translated version of the `.mo` file to include in the package.

Author(s)

Manuel Munoz-Marquez <manuel.munoz@uca.es>

Mantainer: Manuel Munoz-Marquez <manuel.munoz@uca.es>

References

- [1] Brimberg, J. *The Fermat-Weber location problem revisited*, Mathematical Programming, 1, pg. 71-76, 1995. doi:10.1007/BF01592245.
- [2] Love, R. F., Morris, J. G., Wesolowsky, G. O. *Facilities Location: Chapter 2: Introduction to Single-Facility Location*, 1988, North-Holland. ISBN: 0-444-01031-9.
- [3] Weiszfeld, E. and Plastria, F. *On the point for which the sum of the distances to n given points is minimum*, Annals of Operations Research, 167, pg. 7-41, 2009, doi:10.1007/s104790080352z.
- [4] <http://knuth.uca.es/orloca/>

See Also

Para la version en espanol, instale el paquete `orloca.es` y consulte la ayuda sobre [orloca.es-package](#). (For the spanish version, install the `orloca.es` package and see the help about [orloca.es-package](#)).

Examples

```
# A new unweighted loca.p object
o <- loca.p(x = c(-1, 1, 1, -1), y = c(-1, -1, 1, 1))

# Compute the sum of distances to point (3, 4)
distsum(o, 3, 4)

# Compute the sum of distances to point (3, 4) using lp norm
```

```
distsum(o, 3, 4, lp=2.5)

# Solve the optimization problem
distsummin(o)
# Contour plot
contour(o)

# Make a demo of the package
demo(orloca)
```

andalusia

Cities of Andalusia

Description

The 'andalusia' data frame has 12 rows and 4 columns, which are the geographical position of the main capital cities of andalusia.

Format

name: The name of the city or relative position label.
x: The x coordinate of points.
y: The y coordinate of points.
city: If yes the point is a city in other case is a limit.

Usage

```
data('andalusia')
```

Source

The data are taken from wikipedia.

See Also

See also [orloca-package](#).

as-methods

as-methods

Description

Conversions between `loca.p` class and some others classes

Arguments

<code>x</code>	is the object to convert to the new class object.
<code>row.names</code>	Unused.
<code>optional</code>	Unused.
<code>...</code>	Other arguments, unused.

Details

Methods to convert from and to `loca.p` class.

NA's values are not allowed in any of the arguments.

The matrix or data.frame to convert into `loca.p` must have at least two columns. The first column will be consider as the x coordinates, the second as the y coordinates, and the third (if given) as the values of weights `w`.

Value

It returns a new object of the new class.

See Also

See also [loca.p](#)

Examples

```
# A new unweighted loca.p object
loca <- loca.p(x = c(-1, 1, 1, -1), y = c(-1, -1, 1, 1))

# Conversion to matrix
m <- as.matrix(loca)

# Show matrix
m

# Conversion from matrix
as.loca.p(m)
```

as.data.frame.loca.p *as.data.frame.loca.p S3 method to convert from loca.p to data.frame*

Description

Conversions between loca.p class and some others classes

Usage

```
## S3 method for class 'loca.p'
as.data.frame(x, row.names = NULL, optional = FALSE, ...)
```

Arguments

x	is the object to convert to the new class object.
row.names	Unused.
optional	Unused.
...	Other arguments, unused.

Details

Methods to convert from and to loca.p class.

NA's values are not allowed in any of the arguments.

The matrix or data.frame to convert into loca.p must have at least two columns. The first column will be consider as the x coordinates, the second as the y coordinates, and the third (if given) as the values of weights w.

Value

It returns a new object of the new class.

See Also

See also [loca.p](#)

Examples

```
# A new unweighted loca.p object
loca <- loca.p(x = c(-1, 1, 1, -1), y = c(-1, -1, 1, 1))

# Conversion to matrix
m <- as.matrix(loca)

# Show matrix
m

# Conversion from matrix
as.loca.p(m)
```

as.loca.p	<i>as.loca.p</i> The following is for S3 compatibility, mainly for documentation check
-----------	--

Description

Conversions between loca.p class and some others classes

Usage

```
as.loca.p(x, ...)
```

Arguments

x	is the object to convert to the new class object.
...	Other arguments, unused.

Details

Methods to convert from and to loca.p class.

NA's values are not allowed in any of the arguments.

The matrix or data.frame to convert into loca.p must have at least two columns. The first column will be consider as the x coordinates, the second as the y coordinates, and the third (if given) as the values of weights w.

Value

It returns a new object of the new class.

See Also

See also [loca.p](#)

Examples

```
# A new unweighted loca.p object
loca <- loca.p(x = c(-1, 1, 1, -1), y = c(-1, -1, 1, 1))

# Conversion to matrix
m <- as.matrix(loca)

# Show matrix
m

# Conversion from matrix
as.loca.p(m)
```

as.loca.p.data.frame *as.loca.p.data.frame* S3 method to convert from data.frame to loca.p

Description

Conversions between loca.p class and some others classes

Usage

```
as.loca.p.data.frame(x, ...)
```

Arguments

x is the object to convert to the new class object.
... Other arguments, unused.

Details

Methods to convert from and to loca.p class.

NA's values are not allowed in any of the arguments.

The matrix or data.frame to convert into loca.p must have at least two columns. The first column will be consider as the x coordinates, the second as the y coordinates, and the third (if given) as the values of weights w.

Value

It returns a new object of the new class.

See Also

See also [loca.p](#)

Examples

```
# A new unweighted loca.p object
loca <- loca.p(x = c(-1, 1, 1, -1), y = c(-1, -1, 1, 1))

# Conversion to matrix
m <- as.matrix(loca)

# Show matrix
m

# Conversion from matrix
as.loca.p(m)
```

as.loca.p.matrix *as.loca.p.matrix* S3 method to convert from matrix to loca.p

Description

Conversions between loca.p class and some others classes

Usage

```
as.loca.p.matrix(x, ...)
```

Arguments

x is the object to convert to the new class object.
... Other arguments, unused.

Details

Methods to convert from and to loca.p class.

NA's values are not allowed in any of the arguments.

The matrix or data.frame to convert into loca.p must have at least two columns. The first column will be consider as the x coordinates, the second as the y coordinates, and the third (if given) as the values of weights w.

Value

It returns a new object of the new class.

See Also

See also [loca.p](#)

Examples

```
# A new unweighted loca.p object
loca <- loca.p(x = c(-1, 1, 1, -1), y = c(-1, -1, 1, 1))

# Conversion to matrix
m <- as.matrix(loca)

# Show matrix
m

# Conversion from matrix
as.loca.p(m)
```

as.matrix.loca.p *as.matrix.loca.p* S3 method to convert from *loca.p* to matrix

Description

Conversions between *loca.p* class and some others classes

Usage

```
## S3 method for class 'loca.p'  
as.matrix(x, rownames.force = NA, ...)
```

Arguments

x is the object to convert to the new class object.
rownames.force If True the rownames is setted
... Other arguments, unused.

Details

Methods to convert from and to *loca.p* class.

NA's values are not allowed in any of the arguments.

The *matrix* or *data.frame* to convert into *loca.p* must have at least two columns. The first column will be consider as the *x* coordinates, the second as the *y* coordinates, and the third (if given) as the values of weights *w*.

Value

It returns a new object of the new class.

See Also

See also [loca.p](#)

Examples

```
# A new unweighted loca.p object  
loca <- loca.p(x = c(-1, 1, 1, -1), y = c(-1, -1, 1, 1))  
  
# Conversion to matrix  
m <- as.matrix(loca)  
  
# Show matrix  
m  
  
# Conversion from matrix  
as.loca.p(m)
```

contour.loca.p *Plots of the min-sum objective function*

Description

contour provides a graphical representations of min-sum function (distsum).

Usage

```
## S3 method for class 'loca.p'
contour(
  x,
  lp = numeric(0),
  xmin = min(min(x@x), xleft),
  xmax = max(max(x@x), xright),
  ymin = min(min(x@y), ybottom),
  ymax = max(max(x@y), ytop),
  n = 100,
  img = NULL,
  xleft = min(x@x),
  ybottom = min(x@y),
  xright = max(x@x),
  ytop = max(x@y),
  ...
)
```

Arguments

x	The loca.p object to compute the objective.
lp	If given, then l_p norm will be used instead of the Euclidean norm.
xmin	The minimum value for x axis.
xmax	The maximum value for x axis.
ymin	The minimum value for y axis.
ymax	The maximum value for y axis.
n	The number of divisions for grid.
img	A raster image to plot on background.
xleft	The left position of the image.
ybottom	The bottom position of the image.
xright	The right position of the image.
ytop	The top position of the image.
...	Other options.

Details

If $p < 1$ then l_p is not a norm, so only $p \geq 1$ are valid values.

Value

`contour.loca.p` plots a contour plot of min-sum function (`distsum`).

See Also

See also [orloca-package](#), [plot.loca.p](#) and [loca.p](#).

Examples

```
# A new unweighted loca.p object
loca <- loca.p(x = c(-1, 1, 1, -1), y = c(-1, -1, 1, 1))

# The contour plot of min-sum function for loca (a loca.p object)
contour(loca)
```

 distsum

Computes distsum function

Description

The objective function and the gradient function for the min-sum location problem.

Usage

```
distsum(o, x = 0, y = 0, lp = numeric(0))
```

Arguments

<code>o</code>	An object of <code>loca.p</code> class.
<code>x</code>	The x coordinate of the point to be evaluated.
<code>y</code>	The y coordinate of the point to be evaluated.
<code>lp</code>	If given, then l_p norm will be used instead of the Euclidean norm.

Details

The function `zsum` is deprecated and will be removed from new versions of the package.

Value

`distsum` returns the objective function of the min-sum location problem, $\sum_{a_i \in o} w_i d(a_i, (x, y))$, where $d(a_i, (x, y))$ gives the euclidean or the l_p distances between a_i and the point (x, y) .

See Also

See also [orloca-package](#) and [distsummin](#).

Examples

```
# A new unweighted loca.p object
loca <- loca.p(x = c(-1, 1, 1, -1), y = c(-1, -1, 1, 1))
# Evaluation of distsum at (0, 0)
distsum(loca)

# Evaluation of distsum at (1, 3)
distsum(loca, 1, 3)
# Compute the objective function at point (3, 4) using lp norm and p = 2.5
distsum(loca, 3, 4, lp=2.5)
# The gradient function at (1,3)
distsumgra(loca, 1, 3)
```

 distsumgra

Computes the gradient of distsum function

Description

The gradient function for the min-sum location problem.

Usage

```
distsumgra(o, x = 0, y = 0, lp = numeric(0), partial = F)
```

Arguments

<code>o</code>	An object of <code>loca.p</code> class.
<code>x</code>	The x coordinate of the point to be evaluated.
<code>y</code>	The y coordinate of the point to be evaluated.
<code>lp</code>	If given, then l_p norm will be used instead of the Euclidean norm.
<code>partial</code>	If (x,y) is a demand point <code>partial=T</code> means ignore such point to compute the gradient. This option is mainly for internal use.

Details

The function `zsumgra` is deprecated and will be removed from new versions of the package.

Value

`distsumgra` returns the gradient vector of the function of the min-sum location problem, $\sum_{a_i \in o} w_i d(a_i, (x, y))$, where $d(a_i, (x, y))$ gives the euclidean or the l_p distances between a_i and the point (x, y) .

See Also

See also [orloca-package](#) and [distsum](#).

Examples

```
# A new unweighted loca.p object
loca <- loca.p(x = c(-1, 1, 1, -1), y = c(-1, -1, 1, 1))
# Evaluation of distsum at (0, 0)
distsum(loca)

# Evaluation of distsum at (1, 3)
distsum(loca, 1, 3)
# Compute the objective function at point (3, 4) using lp norm and p = 2.5
distsum(loca, 3, 4, lp=2.5)
# The gradient function at (1,3)
distsumgra(loca, 1, 3)
```

distsummin	<i>Returns the solution of the minimization problem</i>
------------	---

Description

Solve the min-sum location problem for a given `loca.p` class object.

Usage

```
distsummin(
  o,
  x = 0,
  y = 0,
  lp = numeric(0),
  max.iter = 1e+05,
  eps = 0.001,
  verbose = FALSE,
  algorithm = "Weiszfeld",
  ...
)
```

Arguments

<code>o</code>	An object of <code>loca.p</code> class.
<code>x</code>	The x coordinate of the starting point. It's default value is 0.
<code>y</code>	The y coordinate of the starting point. It's default value is 0.
<code>lp</code>	If given, the l_p norm will be used instead of the Euclidean norm.
<code>max.iter</code>	Maximum number of iterations allowed. It's default value is 100000.

eps	The module of the gradient in the stop rule. It's default value is 1e-3.
verbose	If TRUE the function produces detailed output. It's default value is FALSE.
algorithm	The method to be use. For this version of the package, the valid values are: "gradient" for a gradient based method, "search" for local search method (this option is deprecated), "ucminf" for optimization with ucminf from ucminf package, and "Weiszfeld" for the Weiszfeld method or any of the valid method for optim function, now "Nelder-Mead", "BFGS", "CG", "L-BFGS-B", "SANN". "Weiszfeld" is the default value.
...	Other options for optimization algorithms.

Details

The algorithms Weiszfeld and gradient include an optimality test for demand points. The Weiszfeld version of the algorithm also implements slow convergence test and accelerator procedure.

If $p < 1$ thus l_p is not a norm, so, only $p \geq 1$ are valid values.

Since l_2 norm is the Euclidean norm, when $p = 2$ `distsumlpmin` are equal to `distsummin`. But the computations involved are greater for the first form.

`max.iter` for SANN algorithm is the number of evaluation of objective function, so this method usually requires large values of `max.iter` to reach optimal value

The function `zsummin` is deprecated and will be removed from new versions of the package.

Value

`distsummin` returns an array with the coordinates of the solution point.

See Also

See also [orloca-package](#), [loca.p](#) and [distsum](#).

Examples

```
# A new unweighted loca.p object
loca <- loca.p(x = c(-1, 1, 1, -1), y = c(-1, -1, 1, 1))
# Compute the minimum
sol<-distsummin(loca)

# Show the result
sol

# Evaluation of the objective function at solution point
distsum(loca, sol[1], sol[2])
```

 loca.p

loca.p class for Operations Research LOCational Analysis

Description

An object of class `loca.p` represents a weighted location problem with a finite demand points set. The [orloca-package](#) is mainly devoted to deals with location problems.

Arguments

<code>x</code>	is a vector of the x coordinates of the demand points.
<code>y</code>	is a vector of the y coordinates of the demand points.
<code>w</code>	is a vector of weights of the demand points. If <code>w</code> is omitted then all weights are considered as 1.
<code>label</code>	If given, it is the label of the new object.

Details

The main generator of the `loca.p` class is `loca.p(x, y, w = numeric(0), label = "")`. An alternative form is `new("loca.p", x, y, w = numeric(0), label = "")`.

The lengths of `x` and `y` vector must be equals. The length of `w` must be equal to the previous ones or must be 0. NA's values are not allowed at any of the arguments.

Value

If the arguments have valid values, it returns a new object of class `loca.p`, else it returns an error. `summary(x)` returns a summary of the `x` `loca.p` object and `print(x)` prints the `x` `loca.p` object in table format.

See Also

See also [orloca-package](#).

Examples

```
# A new unweighted loca.p object
loca <- loca.p(x = c(-1, 1, 1, -1), y = c(-1, -1, 1, 1))
# or
loca <- new("loca.p", x = c(-1, 1, 1, -1), y = c(-1, -1, 1, 1))

# An example with weights and name
locb <- new("loca.p", x = c(-1, 1, 1, -1), y = c(-1, -1, 1, 1),
w = c(1, 2, 1, 2), label = "Weighted case")
```


Description

persp provides a graphical representations of min-sum function (distsum).

Usage

```
## S3 method for class 'loca.p'
persp(
  x,
  lp = numeric(0),
  xmin = min(x@x),
  xmax = max(x@x),
  ymin = min(x@y),
  ymax = max(x@y),
  n = 10,
  ticktype = "detailed",
  ...
)
```

Arguments

x	The loca.p object to compute the objective.
lp	If given, then l_p norm will be used instead of the Euclidean norm.
xmin	The minimum value for x axis.
xmax	The maximum value for x axis.
ymin	The minimum value for y axis.
ymax	The maximum value for y axis.
n	The number of divisions for grid.
ticktype	parameter to pass to low level function persp
...	Other options.

Details

If $p < 1$ then l_p is not a norm, so only $p \geq 1$ are valid values.

Value

A plot a 3D plot or min-sum function.

See Also

See also [orloca-package](#), [plot.loca.p](#) and [loca.p](#).

Examples

```
# A new unweighted loca.p object
loca <- loca.p(x = c(-1, 1, 1, -1), y = c(-1, -1, 1, 1))

# The 3D graphics
persp(loca)
```

plot

plot of loca.p class objects

Description

This method provides a graphical representations of an object of class `loca.p`.

Usage

```
## S3 method for class 'loca.p'
plot(
  x,
  xlab = "",
  ylab = "",
  main = paste(gettext("Plot of loca.p", domain = "R-orloca"), ifelse(x@label == "", "",
    paste0(": \"", x@label, "\""))),
  img = NULL,
  xlim = c(min(xleft, min(x@x)), max(xright, max(x@x))),
  ylim = c(min(ybottom, min(x@y)), max(ytop, max(x@y))),
  xleft = min(x@x),
  ybottom = min(x@y),
  xright = max(x@x),
  ytop = max(x@y),
  ...
)
```

Arguments

<code>x</code>	The <code>loca.p</code> object to plot.
<code>xlab</code>	The label for x axis.
<code>ylab</code>	The label for y axis.
<code>main</code>	The main title for the plot.
<code>img</code>	A raster image to plot on background.
<code>xlim</code>	Limit over the x axes of the plot.
<code>ylim</code>	Limit over the y axes of the plot.
<code>xleft</code>	The left position of the image.
<code>ybottom</code>	The bottom position of the image.

xright The right position of the image.
ytop The top position of the image.
... Other graphical options.

Details

The function plots the demand points with automatic limits evaluation.

Value

The function plots the required graphics.

See Also

See also [orloca-package](#), [loca.p](#) and [plot](#).

Examples

```
# A new unweighted loca.p object  
loca <- loca.p(x = c(-1, 1, 1, -1), y = c(-1, -1, 1, 1))  
# The plot of loca object  
plot(loca)
```

rloca.p

Random instances generator of loca.p class object

Description

rloca.p function returns a random instance of loca.p class object at a given rectangular region.

Usage

```
rloca.p(  
  n,  
  xmin = 0,  
  xmax = 1,  
  ymin = 0,  
  ymax = 1,  
  wmin = 1,  
  wmax = 1,  
  label = "",  
  groups = 0,  
  xgmin = xmin,  
  xgmax = xmax,  
  ygmin = ymin,  
  ygmax = ymax  
)
```

Arguments

n	The number of demand points.
xmin	Minimum value for the x coordinates of the demand points.
xmax	Maximum value for the x coordinates of the demand points.
ymin	Minimum value for the y coordinates of the demand points.
ymax	Maximum value for the y coordinates of the demand points.
wmin	Minimum value for weights
wmax	Maximum value for weights
label	The label for the new loca.p object.
groups	The number of (almost) equal size groups to generate, or a list size of the groups to generate. In the second case n will be ignored.
xgmin	Minimum value for the x coordinate of demand points with respect to the group reference point.
xgmax	Maximum value for the x coordinate of demand points with respect to the group reference point.
ygmin	Minimum value for the y coordinate of demand points with respect to the group reference point.
ygmax	Maximum value for the y coordinate of demand points with respect to the group reference point.

Details

n must be at least 1.

xmin must be less or equal than xmax.

ymin must be less or equal than ymax.

If a non zero value is given for groups parameter, then a reference point for each group are generated. At second stage, the offset part for each demand point are generated, and added to the reference point generated at the first stage.

Note that groups = 1 is not equivalent to the default value groups = 0, because in the first case a reference point are generated at the first stage.

Value

If the arguments are valid values, it returns a new object of loca.p class, else it returns an error.

See Also

See also [orloca-package](#) and loca.p.

Examples

```
# A random loca.p object at unit square with 5 demand points
rloca.p(5)
# At another region
rloca.p(10, xmin=-2, xmax=2, ymin=-2, ymax=2)
# Five groups
rloca.p(48, groups=5)
# Three unequal size groups
rloca.p(1, groups=c(10, 7, 2))
```

zsum

zsum

Description

The function `zsum` is deprecated and could be removed in next version of the package. Use [distsum](#) instead.

Usage

```
zsum(...)
```

Arguments

... Parameters passed to `distsum`

zsumgra

zsumgra

Description

The function `zsumgra` is deprecated and could be removed in next version of the package. Use [distsumgra](#) instead.

Usage

```
zsumgra(...)
```

Arguments

... Parameters passed to `distsumgra`

`zsummin`*zsummin*

Description

The function `zsummin` is deprecated and could be removed in next version of the package. Use [distsummin](#) instead.

Usage

```
zsummin(...)
```

Arguments

... Parameters passed to `distsummin`

Index

- * **andalusia**
 - andalusia, 4
 - * **classes**
 - as-methods, 5
 - contour.locap, 11
 - distsum, 12
 - distsumgra, 13
 - distsummin, 14
 - locap, 16
 - persp.locap, 17
 - plot, 18
 - * **datagen**
 - rlocap, 19
 - * **data**
 - andalusia, 4
 - * **deprecated**
 - zsum, 21
 - zsumgra, 21
 - zsummin, 22
 - * **hplot**
 - contour.locap, 11
 - persp.locap, 17
 - plot, 18
 - * **methods**
 - as-methods, 5
 - * **optimize**
 - distsum, 12
 - distsumgra, 13
 - distsummin, 14
 - locap, 16
 - orloca-package, 2
 - * **package**
 - orloca-package, 2
- andalusia, 4
as-methods, 5
as.data.frame (as-methods), 5
as.data.frame.locap, 6
as.locap, 7
as.locap, data.frame-method (as-methods), 5
as.locap, matrix-method (as-methods), 5
as.locap.data.frame, 8
as.locap.matrix, 9
as.matrix (as-methods), 5
as.matrix.locap, 10
contour.locap, 11
distsum, 12, 14, 15, 21
distsum, locap-method (distsum), 12
distsumgra, 13, 21
distsumgra, locap-method (distsumgra), 13
distsummin, 13, 14, 22
distsummin, locap-method (distsummin), 14
locap, 5–10, 12, 15, 16, 17, 19
orloca-package, 2
persp.locap, 17
plot, 18, 19
plot.locap, 12, 17
print (locap), 16
rlocap, 19
summary (locap), 16
zsum, 21
zsumgra, 21
zsummin, 22